



REVENT DECK OVEN

R FEATURES

Baking quality

- > Superb artisan quality of the baked product with porous natural clay hearth stones
- > 3 zone heat regulation making it easy to adjust the baking profile of the oven and get even bakes
- > Temperature range up to 752° C for flatbread

Total Cost of Ownership

- > Wide variety of sizes rendering a more efficient use of floor space.
- > Programmable easy to use touch control panel.

- > Automatic dampers
- > Auto start
- > Ergonomic and safe handles.
- > Optimized energy efficiency through:
 - Individually controlled decks
 - Heat reflecting glass windows
- > Low service costs.
- > Quick and easy installation.
- > Flexible power supply.
- > Convenient bottom shelf for easy reach of supplies.*
- > Pull-out shelf supporting loading process just when you need it.*
- > Oven legs with castors enabling easy cleaning.

**) Only one shelf delivered with oven. Second shelf is optional.*

Sanitary

Corrosion resistant steam system.

Options

- > 480V power supply available for all models
- > Proofer base
- > Extra pull-out bottom shelf.



In Bread We Trust

US MODEL, tray size 18"x26" 457x660 mm	Max heating capacity Incl control voltage & steam generator	Amps	External measures, inches /mm, width x depth x height	Internal measures, inches / mm, width x depth x height
US 2 deck 2 pan	16.7 kW	49A	58,3" x 35,6" x 32,3" 1480 x 905 x 820 mm	42,0" x 28,0" x 9,6" 1065 x 710 x 245 mm
US 3 deck 2 pan	25.0 kW	73A	58,3" x 35,6" x 45,7" 1480 x 905 x 1160 mm	42,0" x 28,0" x 9,6" 1065 x 710 x 245 mm
US 4 deck 2 pan	33.4 kW	73+25A	58,3" x 35,6" x 59,1" 1480 x 905 x 1500 mm	42,0" x 28,0" x 9,6" 1065 x 710 x 245 mm
US 2 deck 3 pan	22.2 kW	65A	72,3" x 35,6" x 32,3" 1835 x 905 x 820 mm	56,0" x 28,0" x 9,6" 1420 x 710 x 245 mm
US 3 deck 3 pan	33.3 kW	97A	72,3" x 35,6" x 45,7" 1835 x 905 x 1160 mm	56,0" x 28,0" x 9,6" 1420 x 710 x 245 mm
US 4 deck 3 pan	44.3 kW	97+33A	72,3" x 35,6" x 59,1" 1835 x 905 x 1500 mm	56,0" x 28,0" x 9,6" 1420 x 710 x 245 mm

EURO MODEL tray size 23,6"x31,5" 600x800 mm	Max heating capacity Incl control voltage & steam generator	Amps	External measures, inches /mm, width x depth x height	Internal measures, inches / mm, width x depth x height
EUR 1 deck 2 pan	12.3 kW	37A	65,4" x 40,4" x 18,9" 1660 x 1025 x 480 mm	48,4" x 32,3" x 9,6" 1230 x 820 x 245 mm
EUR 2 deck 2 pan	24.7 kW	73A	65,4" x 40,4" x 32,3" 1660 x 1025 x 820 mm	48,4" x 32,3" x 9,6" 1230 x 820 x 245 mm
EUR 3 deck 2 pan	37.0 kW	109A	65,4" x 40,4" x 45,7" 1660 x 1025 x 1160 mm	48,4" x 32,3" x 9,6" 1230 x 820 x 245 mm
EUR 4 deck 2 pan	49.4 kW	109+37A	65,4" x 40,4" x 59,1" 1660 x 1025 x 1500 mm	48,4" x 32,3" x 9,6" 1230 x 820 x 245 mm

MEASURES

Decks	Height legs and castors inches/mm	Canopy inches/mm	Approx weight lbs/kg
1 deck	43,5/1105	2,76/70	440/200
2 decks	36,8/935	2,76/70	770/350
3 decks	30,1/765	2,76/70	1100/500
4 decks	16,7/425	2,76/70	1430/650
5 decks	10,0/255 (no castors)	2,76/70	1760/800

Certifications: UL, UL-C, NSF



Continuous product development is a Revent policy. Therefore, we reserve the right to change specifications and/or design without prior notice. Pictures or drawings may include product options.

Revent sales representative:



Revent Incorporated
100 Ethel Road West, Piscataway, New Jersey 08854
Phone (732) 777-9433, Fax (732) 777-1187
Toll Free 800-822-9642
E-mail info@revent.com, www.revent.com